



Refrigerated Counters

Gastronom 700.....	191
— Advance.....	191
— Concept.....	194
Snack 600.....	207
— Concept.....	207
Pastry 800.....	215
— Concept.....	215

Special units or any variations on the standard model must be assembled at the factory at an additional charge over the standard model's price.

Please, contact Fagor Industrial for any other variation or option that is not included on this list.



Efficiency and quality
for professional needs.



Find out more!







Access the website

We respond to all types of requirement with our broad catalogue of counters.

The Advance range represents Fagor's steadfast commitment to innovation and alignment with the most demanding levels of energy efficiency, obtaining Class A in all refrigeration counters with 2 or 3 doors.

The Concept range is characterised as the more cost-effective line, but with a range breadth unique on the market (GN-700, Snack-600 and Pastry series), thanks to the different options available.

	GASTRONORM - 700		SNACK - 600	PASTRY - 800
	GLOBE ADVANCE	GLOBE CONCEPT	GLOBE CONCEPT	GLOBE CONCEPT
DIMENSIONS (3 doors)	1.800 x 700 x 850	1.792 x 700 x 850	2.017 x 600 x 850	2.017 x 800 x 850
CAPACITY (Nº of levels per door)	6	6	3	10
ENERGY EFFICIENCY CLASS				
INSULATION	60 mm SIDES 50 + 40 mm Double roof	50 mm	50 mm	50 mm
COOLANT	R600a / R290	R600a / R290	R600a / R290	R600a
CLIMATE CLASS	4	4	4	4
AMBIENT TEMPERATURE (*)	43 °C	43 °C	43 °C	43 °C
COOLING SYSTEM	MONOBLOCK	INTERNAL	INTERNAL	INTERNAL CENTRAL
HACCP	YES	NO	NO	NO
ECO MODE	YES	YES	NO	NO
LOCK	IN OPTION Standard with glass doors	IN OPTION Standard with glass doors	IN OPTION Standard with glass doors	IN OPTION
HUMIDITY PROTECTION GRADE	IPX4	IPX4	IPX4	IPX4

(*) AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.

Advance | 700 Gastronorm

ADVANCE counters are available with 700 mm depth and for Gastronorm size containers. ADVANCE counters have been designed to offer an efficient more profitable and sustainable product to improve daily working conditions.



45% ENERGY
SAVING

General characteristics

- High quality austenitic stainless steel inside and outside (except for galvanised back panel).
- 40 kg/m³ injected polyurethane isolation. 60 mm thick side walls, while the ceiling is 40 mm thick with a 50 mm worktop on it to make a total 90 mm thickness.
- Copper piping and aluminium flaps evaporator.
- HACCP system that keeps running logs.
- Digital display for electronic and digital control of temperature and defrosting.
- The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
- Acoustic and visual alarm connected to three sensors at strategic spots. They provide a total control and block the compressor in case of dirt or failure.
- Opened door delay alarm.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
- Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Interior LED lighting (only for models with glass doors).
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: from -2 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- Ambient temperature: 43 °C (*)
- Climatic class 4.

Options:

- Castor kit (factory assembly).
- Without splashback.
- Without worktop.
- Different drawer models.
- Left side cooling unit.
- Panoramic door opening.
- Stainless steel back.
- Granite worktops.
- Heated door frame to avoid condensation in high humidity environments.
- Lock (standard in glass doors).

(*) AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.

Refrigeration
Counters *

Freezer
Counters



EAMFP-225

EAMFN-180

Refrigerated counters
With glass doors



EAMFP-135-PC

Refrigerated
Central counters














EAMCP-180

(*) We can provide granite worktops on our refrigerated counters.
(*) We offer the option of panoramic door opening in models with 2, 3 and 4 doors. (Only solid doors).

VISIBILITY:
Double panel door and anodised aluminium frame with double vacuum chamber.

FLEXIBILITY:
Doors on both sides for enhance flexibility at work.

MODEL	HZ	CODE	NO. OF DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	COOLANT	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS										
 EAMFP-135	50	19037783	2	A	258	381	152	R600a	1.350x700x850	-
 EAMFP-180	50	19037784	3	A	403	514	152	R600a	1.800x700x850	-
 EAMFP-225	50	19037785	4	B	549	810	195	R600a	2.250x700x850	-
Freezer COUNTERS										
 EAMFN-135	50 60	19037806 19074306	2	D -	258	2.044 -	615 699	R290	1.350x700x850	-
 EAMFN-180	50 60	19037809 19074308	3	D -	403	2.654 -	624 708	R290	1.800x700x850	-
Refrigerated COUNTERS with glass doors										
 EAMFP-135-CR-PC	50	19037798	2	-	258	-	178	R600a	1.350x700x850	-
 EAMFP-180-CR-PC	50	19037800	3	-	403	-	180	R600a	1.800x700x850	-
 EAMFP-225-CR-PC	50	19037802	4	-	549	-	203	R600a	2.250x700x850	-
Refrigerated central COUNTERS										
 EAMCP-135	50	19037803	2+2	-	258	-	174	R600a	1.350x768x850	-
 EAMCP-180	50	19037804	3+3	-	403	-	174	R600a	1.800x768x850	-
 EAMCP-225	50	19037805	4+4	-	546	-	195	R600a	2.250x768x850	-

Refrigerated counters With drawers *



EAMFP-225-HHHD



EAMFP-180-TTT

VERSATILITY:

Different sets of drawers for the most specific requirements.

ROBUSTNESS:

Our bottom perforated drawers can stand up to 40 kg.

* We have different versions of drawer kits and doors available:
Set 2 drawers (H), Set 3 drawers (T) and Doors (D).

	MODEL	CODE	NO. OF DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	COOLANT	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH "H" DRAWERS										
	EAMFP-135-HD	19037786	1 H 1 D	A	258	381	152	R600a	1.350x700x850	-
	EAMFP-135-HH	19037789	2 H	A	258	381	152	R600a	1.350x700x850	-
	EAMFP-180-HDD	19037790	1 H 2 D	A	403	514	173	R600a	1.800x700x850	-
	EAMFP-180-HHD	19037791	2 H 1 D	A	403	514	173	R600a	1.800x700x850	-
	EAMFP-180-HHH	19037792	3 H	A	403	514	173	R600a	1.800x700x850	-
	EAMFP-225-HDDD	19037793	1 H 3 D	B	549	810	195	R600a	2.250x700x850	-
	EAMFP-225-HHDD	19037795	2 H 2 D	B	549	810	195	R600a	2.250x700x850	-
	EAMFP-225-HHHD	19037796	3 H 1 D	B	549	810	195	R600a	2.250x700x850	-
	EAMFP-225-HHHH	19037797	4 H	B	549	810	195	R600a	2.250x700x850	-
REFRIGERATED COUNTERS WITH "T" DRAWERS										
	EAMFP-135-TT	19048245	3T	A	258	381	152	R600a	1.350x700x850	-
	EAMFP-180-TTT	19058976	3T	A	403	514	152	R600a	1.800x700x850	-

Drawers for refrigerated counters

	MODEL	KIT	CODE	TYPE OF COUNTER	POSITION OF THE KIT IN THE UNIT	€
	KIT 2 DRAWERS (1/2+1/2)	H	19012537	ADVANCE Gastronorm		-
	KIT 2 DRAWERS (1/3+2/3)	W	19012538	ADVANCE Gastronorm		-
	KIT 3 DRAWERS (1/3+1/3+1/3)	T	19012539	ADVANCE Gastronorm		-

Concept | 700 Gastronorm

Our 700 mm deep CONCEPT range with capacity for Gastronorm containers provides one of the widest refrigerated counter choices in the market. We provide a wide range of versions and options to suit every user's needs with a robust, ergonomic, functional and easy to clean product.



35% ENERGY
SAVING WITH HC
COOLANTS

General characteristics

- High quality austenitic stainless steel inside and outside (except for galvanised back panel).
- 50 mm, 40 kg/m³ injected polyurethane insulation.
- Forced draught cooling system inside the room.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
- Opened door delay alarm.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
- Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Interior LED lighting (only for models with glass doors).
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: from -2 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- Ambient temperature: 43 °C (*)
- Climatic class 4.

Options:

- Castor kit (factory assembly).
- Without splashback.
- Without worktop.
- Different drawer models.
- Left side cooling unit.
- Panoramic door opening.
- Stainless steel back.
- Granite worktops.
- Heated door frame to avoid condensation in high humidity environments.
- Lock (standard in glass doors).

(*) AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.

Refrigerated counters

Refrigerated Counters









EMFP-135-GN

Refrigerated counters With pre-installation



EMFP-192-GN-R

ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€	
REFRIGERATED COUNTERS											
	EMFP-135-GN	R600a R290	50	19036976	2	B	274	752	203	1.342x700x850	-
			60	19073998							
	EMFP-180-GN	R600a R290	50	19036983	3	C	428	931	203	1.792x700x850	-
			60	19074329							
	EMFP-225-GN	R600a	50	19036995	4	C	581	1.096	224	2.242x700x850	-
			60	19073991							
REFRIGERATED COUNTERS WITH PRE-INSTALLATION											
	EMFP-102-GN-R	-	50/60	19037590	2	-	274	-	29	1.042x700x850	-
	EMFP-147-GN-R	-	50/60	19037591	3	-	428	-	29	1.492x700x850	-
	EMFP-192-GN-R	-	50/60	19037592	4	-	581	-	29	1.942x700x850	-

Freezer counters

Freezer Counters

Freezer counters With pre-installation



EMFN-180-GN



EMFN-102-GN-R

ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
FREEZER COUNTERS											
🚚	EMFN-135-GN	R290	50	19037545	2	D	274	2.212	667	1.342x700x850	-
			60	19074330		-		737			
🚚	EMFN-180-GN	R290	50	19037550	3	D	428	2.467	676	1.792x700x850	-
			60	19073268		-		746			
FREEZER COUNTERS WITH PRE-INSTALLATION											
	EMFN-102-GN-R		50/60	19037636	2	-	274	-	414	1.042x700x850	-
	EMFN-147-GN-R		50/60	19037637	3	-	428	-	423	1.492x700x850	-

Refrigerated counters With drawers (*)












EMFP-180-GN HHH













EMFP-135-GN HD

ROBUSTNESS:
Our perforated stainless steel drawers
can stand loads up to 40 kg.

(*) We have different versions of drawer kits
and doors available
Set 2 drawers (H)
Doors (D)

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH DRAWERS										
 EMFP-135-GN HD	R600a	50	19036978	1 H 1 D	C	274	752	203	1.342x700x850	-
 EMFP-135-GN HH	R600a	50	19036979	2 H	C		752	203		-
 EMFP-180-GN HDD	R600a	50	19036985	1 H 2 D	C	428	931	203	1.792x700x850	-
 EMFP-180-GN HHD	R600a	50	19036986	2 H 1 D	C		931	203		-
 EMFP-180-GN HHH	R600a	50	19036992	3 H	C	931	203	-		-
 EMFP-225-GN HDDD	R600a	50	19036997	1 H 3 D	C	581	1.096	224	2.242x700x850	-
 EMFP-225-GN HHDD	R600a	50	19036998	2 H 2 D	C		1.096	224		-
 EMFP-225-GN HHHH	R600a	50	19036999	3 H 1 D	C		1.096	224		-
 EMFP-225-GN HHHH	R600a	50	19037000	4 H	C	1.096	224	-		-

Drawers for refrigerated counters










MODEL	KIT	CODE	TYPE OF COUNTER	POSITION OF THE KIT IN THE UNIT	€
 KIT 2 DRAWERS (1/2+1/2)	H	19010993	CONCEPT Gastronorm		-
 KIT 2 DRAWERS (1/2+1/2) RIGHT	H	19015952	CONCEPT Gastronorm		-
 KIT 2 DRAWERS (1/2+1/2) LEFT	H	19036401	CONCEPT Gastronorm		-
 KIT 2 DRAWERS (1/3+2/3)	W	19015953	CONCEPT Gastronorm		-
 KIT 3 DRAWERS (1/3+1/3+1/3)	T	19015954	CONCEPT Gastronorm		-

Refrigerated counters with drawers And pre-installation



EMFP-192-GN HHDD-R

ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH DRAWERS WITH PRE-INSTALLATION										
 EMFP-102-GN-R HD	-	50/60	19037613	1 H 1 D	-	274	-	-	1.042x700x850	-
 EMFP-102-GN-R HH	-	50/60	19037615	2 H	-		-	-		-
 EMFP-147-GN-R HDD	-	50/60	19037616	1 H 2 D	-	428	-	-	1.492x700x850	-
 EMFP-147-GN-R HHD	-	50/60	19037619	2 H 1 D	-		-	-		-
 EMFP-147-GN-R HHH	-	50/60	19037630	3 H	-	-	-	-	-	-
 EMFP-192-GN-R HDDD	-	50/60	19037631	1 H 3 D	-	581	-	-	1.942x700x850	-
 EMFP-192-GN-R HHDD	-	50/60	19037632	2 H 2 D	-		-	-		-
 EMFP-192-GN-R HHHD	-	50/60	19037633	3 H 1 D	-		-	-		-
 EMFP-192-GN-R HHHH	-	50/60	19037635	4 H	-		-	-		-

Refrigerated counters with glass doors

Refrigerated counters With glass doors



EMFP-180-GN CR PC







VISIBILITY:
Double pane door and anodised aluminium frame
with double vacuum chamber.

Refrigerated counters With glass doors and pre-installation



EMFP-102-GN-R CR PC

ADAPTABILITY:
Units ready for the connection of a remote cooling unit.
The cooling unit is not included.

MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH GLASS DOORS										
 EMFP-135-GN CR PC	R600a	50	19036977	2	-	274	-	205	1.342x700x850	-
 EMFP-180-GN CR PC	R600a	50	19036984	3	-	428	-	207	1.792x700x850	-
 EMFP-225-GN CR PC	R600a	50	19036996	4	-	581	-	230	2.242x700x850	-
REFRIGERATED COUNTERS WITH GLASS DOORS AND PRE-INSTALLATION										
 EMFP-102-GN-R CR PC	-	50/60	19037609	2	-	274	-	-	1.042x700x850	-
 EMFP-147-GN-R CR PC	-	50/60	19037611	3	-	428	-	-	1.492x700x850	-
 EMFP-192-GN-R CR PC	-	50/60	19037612	4	-	581	-	-	1.942x700x850	-

Refrigerated counters With sink



EMFP-225-GN F

SINK:
(330 x 365 x 140 mm) sink included
with rinse grid on the worktop.

Refrigerated Central counters



EMCP-180-GN

FLEXIBILITY:
Doors on both sides for easier reaching in.

Refrigerated counters with sink

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH SINK											
	EMFP-135-GN-F	R600a	50	19036982	2	B	274	752	203	1.342x700x850	-
	EMFP-180-GN-F	R600a	50	19036993	3	C	428	931	203	1.792x700x850	-
	EMFP-225-GN-F	R600a	50	19037001	4	C	581	1.096	224	2.242x700x850	-

Refrigerated central counters

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED CENTRAL COUNTERS											
	EMCP-135-GN	R600a	50	19037012	2+2	-	274	-	203	1.342x768x850	-
	EMCP-180-GN	R600a	50	19037013	3+3	-	428	-	203	1.792x768x850	-
	EMCP-225-GN	R600a	50	19037014	4+4	-	581	-	224	2.242x768x850	-

Refrigerated bases

Intended to give support to counter top cooking equipment. Ideal for refrigeration solutions in small rooms.

Models with doors



EMFP-180-BP

Models with drawers 1/3 et 2/3



EMFP-180-B2

	MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED BASES WITH DOORS											
	EMFP-135-BP	R600a R290	50	19037038	2	C	177	752	202	1.342x700x584	-
			60	19074511							
	EMFP-180-BP	R600a R290	50	19037042	3	C	277	931	202	1.792x700x584	-
			60	19074512							
	EMFP-225-BP	R600a	50	19037048	4	D	377	1096	224	2.242x700x584	-
			60	19074515							
REFRIGERATED BASES WITH 2/3 DRAWERS											
	EMFP-135-B	R600a R290	50	19037039	2 x 2/3	C	177	752	202	1.342x700x584	-
			60	19074511							
	EMFP-180-B	R600a R290	50	19037043	3 x 2/3	C	277	931	202	1.792x700x584	-
			60	19074512							
	EMFP-225-B	R600a	50	19037049	4 x 2/3	C	377	1.096	224	2.242x700x584	-
			60	19074515							
REFRIGERATED BASES WITH 1/3 AND 2/3 DRAWERS											
	EMFP-135-B2	R600a R290	50	19037040	2 x 1/3 1 x 2/3	C	177	752	202	1.342x700x584	-
			60	19074511							
	EMFP-180-B2	R600a R290	50	19037044	4 x 1/3 1 x 2/3	C	277	931	202	1.792x700x584	-
			60	19074512							
	EMFP-225-B2	R600a	50	19037050	6 x 1/3 1 x 2/3	D	377	1.096	224	2.242x700x584	-
			60	19074515							

Refrigerated stands Kore 900



General characteristics

- Sealed compressor with ventilated condenser.
- Copper pipe evaporator with aluminum wings.
- 50 mm injected polyurethane insulation with a density of 40kg/m³.
- BP models with panoramic door opening and automatic closing device with stay open feature above 90°.
- Height adjustable stainless-steel legs (from 130mm to 190mm) allows adjusting the overall height of the counter from 580 to 640mm.

- Forced air refrigeration system
- Working temperature: -2 °C, +8 °C, at room temperature of 38 °C.
- Climate Class 4
- Electronic temperature and defrosting control and display.
- BP model with doors and B model with GN 1/1 holding capacity drawers.
- BH model with a full-length flat drawer with GN2/1 holding capacity and equipped with 5 crosspieces to support different combinations of GN containers.

- Options:
- Kit of 6 castors (2 with brakes). Factory fitted.
 - 60Hz

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER(W)	DIMENSIONS (MM)	€
MODELS WITH DOORS										
EMFP9-120 BP	R290	50	19048089	2	C	169	714	250	1.200x900x590	-
MODELS WITH 2/3 DRAWERS										
EMFP9-120 B	R290	50	19048090	2 x 2/3	C	169	714	250	1.200x900x590	-
MODELS WITH FULL LENGTH FLAT DRAWERS										
EMFP9-120 BH	R290	50	19047995	2 x GN 2/1	C	169	777	250	1.200x900x590	-

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER(W)	DIMENSIONS (MM)	€
MODELS WITH DOORS										
EMFP9-160 BP	R290	50	19068878	3	C	240	1113	250	1.600x900x590	-
MODELS WITH 2/3 DRAWERS										
EMFP9-160 B	R290	50	19068870	3 x GN 1/1	C	240	1113	250	1.600x900x590	-

Refrigerated stands

General characteristics

- Sealed compressor with ventilated condenser.
 - Copper pipe evaporator with aluminum wings.
 - 50 mm injected polyurethane insulation with a density of 40kg/m³.
 - BP models with panoramic door opening and automatic closing device with stay open feature above 90°.
 - Height adjustable stainless-steel legs (from 130mm to 190mm) allows adjusting the overall height of the counter from 580 to 640mm.
 - Forced air refrigeration system.
 - Working temperature: -2 °C, +8 °C, at room temperature of 38 °C.
 - Climate Class 4.
 - Electronic temperature and defrosting control and display.
 - BP model with doors and B model with GN 2/3 holding capacity drawers.
 - BH model with a full-length flat drawer with 2XGN2/3 holding capacity and equipped with 5 crosspieces to support different combinations of GN containers.
- Options:
- Kit of 6 castors (2 with brakes). Factory fitted.
 - 60Hz.

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER(W)	DIMENSIONS (MM)	€
MODELS WITH DOORS										
EMFP7-120 BP	R290	50	19074945	2	C	110	657	250	1200x630x590	-
MODELS WITH 2/3 DRAWERS										
EMFP7-120 B	R290	50	19074943	2 x GN 2/3	C	110	657	250	1200x630x590	-
MODELS WITH FULL LENGTH FLAT DRAWERS										
EMFP7-120 BH	R290	50	19075072	2 x GN 4/3	c	110	777	250	1200x630x590	-

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER(W)	DIMENSIONS (MM)	€
MODELS WITH DOORS										
EMFP7-160 BP	R290	50	19076353	3	C	169	1113	250	1.600x630x590	-
MODELS WITH 2/3 DRAWERS										
EMFP7-160 B	R290	50	19076352	3 x GN 2/3	C	169	1113	250	1.600x630x590	-

















GN counters - available options and price increase per model

MODEL	ST. STEEL BACK PANEL (€)	3 CM GRANITE WORKTOP (€)	WITHOUT WORKTOP (€)	WITHOUT SPLASHBACK (€)	WHEELS SET (€)	LOCK (PER DOOR) (€)	DRAWERS SET [1/2] UNIT (€)	DRAWERS SET [1/3] UNIT (€)	COMPRESSOR ON THE LEFT (€)	HEATED DOOR FRAME (€)	PANORAMIC OPENING (€)
	RI	GR	SE	SP	R	CR	H	T	GI	T	AP
ADVANCE - 700 GASTRONORM											
EAMFP-135 GN	0	0	0	0	0	0	0	0	-	0	0
EAMFP-180 GN	0	0	0	0	0	0	0	0	-	0	0
EAMFP-225 GN	0	0	0	0	0	0	0	0	-	0	0
EAMFN-135 GN	0	0	0	0	0	0	-	-	-	STD	0
EAMFN-180 GN	0	0	0	0	0	0	-	-	-	STD	0
EAMFP-135 GN-PC	0	0	0	0	0	STD	-	-	-	0	-
EAMFP-180 GN-PC	0	0	0	0	0	STD	-	-	-	0	-
EAMFP-225 GN-PC	0	0	0	0	0	STD	-	-	-	0	-
EAMCP-135 GN	-	0	0	STD	0	0	-	-	-	0	0
EAMCP-180 GN	-	0	0	STD	0	0	-	-	-	0	0
EAMCP-225 GN	-	0	0	STD	0	0	-	-	-	0	0
CONCEPT - 700 GASTRONORM											
EMFP-135 GN	0	0	0	0	0	0	0	0	0	0	0
EMFP-180 GN	0	0	0	0	0	0	0	0	0	0	0
EMFP-225 GN	0	0	0	0	0	0	0	0	0	0	0
EMFN-135 GN	0	0	0	0	0	0	-	-	0	STD	0
EMFN-180 GN	0	0	0	0	0	0	-	-	0	STD	0
EMFP-135 GN-PC	0	0	0	0	0	STD	-	-	0	0	-
EMFP-180 GN-PC	0	0	0	0	0	STD	-	-	0	0	-
EMFP-225 GN-PC	0	0	0	0	0	STD	-	-	0	0	-
EMFP-135 GN-F	0	-	-	0	-	0	0	0	-	0	0
EMFP-180 GN-F	0	-	-	0	-	0	0	0	-	0	0
EMFP-225 GN-F	0	-	-	0	-	0	0	0	-	0	0
EMFP-135 BP	0	-	-	STD	0	0	-	-	-	0	-
EMFP-180 BP	0	-	-	STD	0	0	-	-	-	0	-
EMFP-225 BP	0	-	-	STD	0	0	-	-	-	0	-
EMCP-135 GN	-	0	0	STD	0	0	-	-	-	0	0
EMCP-180 GN	-	0	0	STD	0	0	-	-	-	0	0
EMCP-225 GN	-	0	0	STD	0	0	-	-	-	0	0
EMFP-102 GN-R	0	0	0	0	-	0	0	0	-	0	0
EMFP-147 GN-R	0	0	0	0	-	0	0	0	-	0	0
EMFP-192 GN-R	0	0	0	0	-	0	0	0	-	0	0
EMFN-102 GN-R	0	0	0	0	-	0	-	-	-	0	0
EMFN-147 GN-R	0	0	0	0	-	0	-	-	-	0	0
EMFP-102 GN-R PC	0	0	0	0	-	STD	-	-	-	0	-
EMFP-147 GN-R PC	0	0	0	0	-	STD	-	-	-	0	-
EMFP-192 GN-R PC	0	0	0	0	-	STD	-	-	-	0	-

* Applies to all refrigeration front counters (B, BP, B2).

Drawers for refrigerated counters

MODEL	KIT	CODE	TYPE OF COUNTER	POSITION OF THE KIT IN THE UNIT	€
 KIT 2 DRAWERS (1/2+1/2)	H	19012537	ADVANCE Gastronorm		-
 KIT 2 DRAWERS (1/3+2/3)	W	19012538	ADVANCE Gastronorm		-
 KIT 3 DRAWERS (1/3+1/3+1/3)	T	19012539	ADVANCE Gastronorm		-
KIT 2 DRAWERS (1/2+1/2)	H	19010993	CONCEPT Gastronorm		-
 KIT 2 DRAWERS (1/2+1/2) RIGHT	H	19015952	CONCEPT Gastronorm		-
KIT 2 DRAWERS (1/2+1/2) LEFT	H	19036401	CONCEPT Gastronorm		-
 KIT 2 DRAWERS (1/3+2/3)	W	19015953	CONCEPT Gastronorm		-
 KIT 3 DRAWERS (1/3+1/3+1/3)	T	19015954	CONCEPT Gastronorm		-

Kits castors to assembly

DESCRIPTION	CODE	€
KIT 4 WHEELS, 2 with bracked	19016846	-
KIT 6 WHEELS, 3 with bracked	19011005	-

Accessories for gn counters *


DESCRIPTION	CODE
GRID GN 1/1 Epoxi (530x325)	12035781
GRID GN 1/1 Stainless steel (530x325)	19000999
GUIDE for grid GN-1/1 - Side grid - 562 mm - 1 element	12037936
GUIDE for grid GN-1/1 - Central grid - 612 mm - 1 element	12036716
GUIDE for grid GN-1/1 - ADVANCE counters - Side and Central - 519 mm - 1 element	12036880

* Check prices at accessories and spare parts list

Panoramic Opening (AP)



(#) PANORAMIC OPENING - possible OPTIONS



Concept | 600 Snack

Our 600 mm deep CONCEPT range with Snack dimensions offers a wide choice of refrigerated counter worktops to fit into reduced spaces with a robust, ergonomic, functional and easy to clean product.



60% ENERGY
SAVING WITH HC
COOLANTS

General characteristics

- High quality austenitic stainless steel inside and outside (except for galvanised back panel).
- 50 mm, 40 kg/m³ injected polyurethane insulation.
- Forced draught cooling system inside the room.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning.

- Grid self-dimensions: 405 x 460 mm.
- Equipment: 1 grid per door and 1 set of tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Interior LED lighting (only for models with glass doors).
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: from -2 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
- Ambient temperature: 43 °C (*)
- Climatic class 4.

- Options:
- Castor kit (factory assembly).
 - Without splashback.
 - Without worktop.
 - Different drawer models.
 - Left side cooling unit.
 - Panoramic door opening.
 - Stainless steel back.
 - Lock (standard in glass doors).
 - Heated door frame to avoid condensation in high humidity environments.

(*) AMBIENT TEMPERATURE: Guaranteed operation at 43°C. Excluded display models with glass doors. For specific intensive usage please check with Fagor Commercial Manager.



Refrigerated counters

Refrigerated
Counters

EMSP-150

Refrigerated counters
With pre-installation (*)

EMSP-169-R

* ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS											
	EMSP-150	R600a R290	50	19036912	2	C	268	836	203	1.492x600x850	-
			60	19074528		-		-	295		
	EMSP-200	R600a R290	50	19036970	3	C	416	931	203	2.017x600x850	-
			60	19074529		-		-	295		
	EMSP-250	R600a	50	19037002	4	C	564	1.096	224	2.542x600x850	-
			60	19074530		-		-	241		
REFRIGERATED COUNTERS WITH PRE-INSTALLATION											
	EMSP-117-R	-	50/60	19037640	2	-	268	-	-	1.192x600x850	-
	EMSP-169-R	-	50/60	19037641	3	-	416	-	-	1.717x600x850	-
	EMSP-222-R	-	50/60	19037642	4	-	564	-	-	2.242x600x850	-

Freezer counters

Freezer Counters







EMSN-200-GN

Freezer counters With pre-installation (*)



EMSN-117-R

* ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
FREEZER COUNTERS										
 EMSN-150	R290	50	19037552	2	D	268	2.212	669	1.492x600x850	-
		60	19074531							
 EMSN-200	R290	50	19037553	3	D	416	2.467	679	2.017x600x850	-
		60	19074532							
FREEZER COUNTERS WITH PRE-INSTALLATION										
 EMSN-117-R	-	50/60	19037666	2	-	268	-	416	1.192x600x850	-
 EMSN-169-R	-	50/60	19037668	3	-	416	-	426	1.717x600x850	-

Refrigerated counters with drawers



ROBUSTNESS:
Our perforated stainless steel drawers
can stand loads up to 40 kg.

We have different versions of drawer kits and doors available
Set 2 drawers (H)
Doors (D)

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€	
REFRIGERATED COUNTERS WITH DRAWERS											
	EMSP-150-HD	R600a	50	19036948	1 H 1 D	C	268	836	203	1.492x600x850	-
	EMSP-150-HH	R600a	50	19036953	2 H	C		836	203	-	
	EMSP-200-HDD	R600a	50	19036973	1 H 2 D	C	416	931	203	-	
	EMSP-200-HHD	R600a	50	19036974	2 H 1 D	C		931	203	2.017x600x850	-
	EMSP-200-HHH	R600a	50	19036975	3 H	C		931	203	-	
	EMSP-250-HDDD	R600a	50	19037006	1 H 3 D	C		1.096	224	-	
	EMSP-250-HHDD	R600a	50	19037007	2 H 2 D	C	564	1.096	224	2.542x600x850	-
	EMSP-250-HHHD	R600a	50	19037008	3 H 1 D	C		1.096	224	-	
	EMSP-250-HHHH	R600a	50	19037009	4 H	C		1.096	224	-	










Drawers for snack refrigerated counters

MODEL	KIT	CODE	TYPE OF COUNTER	POSITION OF THE KIT IN THE UNIT	€
	KIT 2 DRAWERS (1/2+1/2)	H	19004925	Snack	-
	KIT 2 DRAWERS (1/2+1/2) RIGHT	H	19004921	Snack	-
	KIT 2 DRAWERS (1/2+1/2) LEFT	H	19004930	Snack	-
	KIT 2 DRAWERS (1/3+2/3)	W	19004927	Snack	-
	KIT 3 DRAWERS (1/3+1/3+1/3)	T	19004923	Snack	-

Refrigerated counters with drawers and pre-installation



ADAPTABILITY:
Units ready for the connection
of a remote cooling unit.
The cooling unit is not included.

MODEL	COOLANT	HZ.	CODE	N. DOORS AND DRAWERS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
REFRIGERATED COUNTERS WITH DRAWERS AND PRE-INSTALLATION										
 EMSP-117-R HD	-	50/60	19037645	1 H 1 D	-	268	-	-	1.192x600x850	-
 EMSP-117-R HH	-	50/60	19037646	2 H	-	268	-	-	1.192x600x850	-
 EMSP-169-R HDD	-	50/60	19037648	1 H 2 D	-	416	-	-	1.717x600x850	-
 EMSP-169-R HHD	-	50/60	19037649	2 H 1 D	-	416	-	-	1.717x600x850	-
 EMSP-169-R HHH	-	50/60	19037650	3 H	-	416	-	-	1.717x600x850	-
 EMSP-222-R HDDD	-	50/60	19037651	1 H 3 D	-	564	-	-	2.242x600x850	-
 EMSP-222-R HHDD	-	50/60	19037652	2 H 2 D	-	564	-	-	2.242x600x850	-
 EMSP-222-R HHHD	-	50/60	19037654	3 H 1 D	-	564	-	-	2.242x600x850	-
 EMSP-222-R HHHH	-	50/60	19037655	4 H	-	564	-	-	2.242x600x850	-

Refrigerated counters with glass doors

Refrigerated counters
With glass doors

EMSP-150-PC

VISIBILITY:
Double pane door and anodised aluminium frame with double vacuum chamber.

Refrigerated counters
With sink

EMSP-150-F

SINK:
Sink dimensions: 330 x 365 x 140 mm









Refrigerated counters with glass doors

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
	EMSP-150-CR-PC	R600a	50	19036937	2	-	268	-	207	1.492x600x850	-
	EMSP-200-CR-PC	R600a	50	19036972	3	-	416	-	209	2.017x600x850	-
	EMSP-250-CR-PC	R600a	50	19037004	4	-	564	-	232	2.542x600x850	-

Refrigerated counters with sink

	MODEL	COOLANT	HZ.	CODE	N. DOORS	ENERGY EFFICIENCY CLASS	GROSS CAPACITY (L)	ANNUAL ENERGY CONSUMPTION (KW-H)	ELECTRIC POWER (W)	DIMENSIONS (MM)	€
	EMSP-150-F	R600a	50	19036915	2	C	268	836	203	1.492x600x850	-
	EMSP-200-F	R600a	50	19036971	3	C	416	931	203	2.017x600x850	-
	EMSP-250-F	R600a	50	19037003	4	C	564	1.096	224	2.542x600x850	-


Drawers for snack refrigerated counters

MODEL	KIT	CODE	TYPE OF COUNTER	POSITION OF THE KIT IN THE UNIT	€
KIT 2 DRAWERS (1/2+1/2)	H	19004925	Snack		-
 KIT 2 DRAWERS (1/2+1/2) RIGHT	H	19004921	Snack		-
KIT 2 DRAWERS (1/2+1/2) LEFT	H	19004930	Snack		-
 KIT 2 DRAWERS (1/3+2/3)	W	19004927	Snack		-
 KIT 3 DRAWERS (1/3+1/3+1/3)	T	19004923	Snack		-

Snack counters - available options and price increase per model

MODEL	ST. STEEL BACK PANEL (€)	3 CM GRANITE WORKTOP (€)	WITHOUT WORKTOP (€)	WITHOUT SPLASHBACK (€)	WHEELS SET (€)	LOCK (PER DOOR) (€)	DRAWERS SET [1/2] UNIT (€)	DRAWERS SET [1/3] UNIT (€)	COMPRESSOR ON THE LEFT (€)	HEATED DOR FRAME (€)	PANORAMIC OPENING (€)
	RI	GR	SE	SP	R	CR	H/W	T	GI	T	AP
GLOBE - 600 SNACK											(#)
EMSP-150	0	-	0	0	0	0	0	0	0	0	0
EMSP-200	0	-	0	0	0	0	0	0	0	0	0
EMSP-250	0	-	0	0	0	0	0	0	0	0	0
EMSN-150	0	-	0	0	0	0	-	-	0	Std	0
EMSN-200	0	-	0	0	0	0	-	-	0	Std	0
EMSP-150-PC	0	-	0	0	0	Std	-	-	0	0	-
EMSP-200-PC	0	-	0	0	0	Std	-	-	0	0	-
EMSP-250-PC	0	-	0	0	0	Std	-	-	0	0	-
EMSP-150-F	0	-	-	0	-	0	0	0	-	0	0
EMSP-200-F	0	-	-	0	-	0	0	0	-	0	0
EMSP-250-F	0	-	-	0	-	0	0	0	-	0	0
EMSP-117-R	0	-	0	0	-	0	0	0	-	0	0
EMSP-169-R	0	-	0	0	-	0	0	0	-	0	0
EMSP-222-R	0	-	0	0	-	0	0	0	-	0	0
EMSN-117-R	0	-	0	0	-	0	-	-	-	Std	0
EMSN-169-R	0	-	0	0	-	0	-	-	-	Std	0

(#) PANORAMIC OPENING - possible OPTIONS



Kit castors for counters

DESCRIPTION	CODE	€
KIT 4 WHEELS Ø 80, 2 with bracket - For 2 and 3 doors counters	19016846	-
KIT 6 WHEELS Ø 80, 3 with bracket - For 4 doors counters	19011005	-

Accessories *

DESCRIPTION	CODE
Side GRID Epoxi (405x460)	12034975
Central GRID Epoxi (405x525)	12034847
Support for Snack GRID	12037728

* Check prices at accessories and spare parts list




Concept | Pastry counters - depth 800 mm

Pastry counters complete our offer for equipment specially designed for this industry.



General characteristics

- High quality austenitic stainless steel inside and outside (except for galvanised back panel).
- 50 mm, 40 kg/m³ injected polyurethane insulation.
- Natural draught cooling system.
- Vertical evaporator to allow a larger storage capacity.
- Digital display for electronic and digital control of temperature and defrosting.
- The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
- Opened door delay alarm.
- Easier loading and unloading thanks to its door self-closing and stay open features.
- Removable and height adjustable plastic covered steel shelves for easy cleaning (600 x 400 mm).
- Equipment per door: 1 600 x 400 mm grid and 2 sets of height adjustable tray slides.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- 10 cm high splashback.
- Working temperature: -2 °C, +8 °C.
- Ambient temperature: 43 °C (*)
- Climatic class 4.


MODEL	HZ.	CODE	NO. OF DOORS	GROSS CAPACITY (L)	ELECTRIC POWER (W)	COOLANT	DIMENSIONS (MM)	€
 EMPP-150-GV	50	19037745	2	376	220	R290	1.492x800x850	-
 EMPP-202-GV	50	19037746	3	584	303	R290	2.017x800x850	-
 EMPP-255-GV	50	19037747	4	792	303	R290	2.542x800x850	-

(*) AMBIENT TEMPERATURE: Guaranteed operation at 43°C. For specific intensive usage please check with Fagor Commercial Manager.

Pastry counters - available options and price increase per model

MODEL	ST. STEEL BACK PANEL RI	3 CM GRANITE WORKTOP GR	WITHOUT WORKTOP SE	WITHOUT SPLASHBACK SP	WHEELS SET	LOCK (PER DOOR)	HEATED DOOR FRAME	PANORAMIC OPENING (#)
	(€)	(€)	(€)	(€)	(€)	(€)	(€)	(€)
EMPP-150	-	-	-	-	-	-	-	-
EMPP-202	-	-	-	-	-	-	-	-
EMPP-255	-	-	-	-	-	-	-	-

(#) Panoramic opening - possible options



Kit castors for counters

DESCRIPTION	CODE	€
KIT 4 WHEELS Ø 80, 2 with bracket - For 2 and 3 doors counters	19016846	-
KIT 6 WHEELS Ø 80, 3 with bracket - For 4 doors counters	19011005	-

Accessories *

DESCRIPTION	CODE
GRID - Epoxi (600x400)	12034886
GRID - Stainless steel, (600x400)	19001001
PASTRY CONTAINER - Stainless steel, (600x400)	19010201
SIDE GUIDE for grid - 649 mm - 1 element	12036419
CENTRAL GUIDE for grid - 711 mm - 1 element	12038109

* Assembly available on demand.