



Flatwork ironers



Quality ironing recognised by users



Unique solutions for any space

Fagor Professional presents a wide range of wall-flatwork ironer, the perfect and innovative solution for drying, ironing and folding flatwork, for every type of customer.

Fagor Professional's flatwork ironers are designed to offer optimum performance and productivity with significant energy efficiency options and savings in time. For example, the Smart system (moisture control), the Touch Plus Control TP2 (only in Ø 500/650 mm models) and the multiple notable features: radiant gas burner, rear delivery, length folder, connectivity, versatility, etc.

There are four main ranges: Ø 200 and 325 mm / Ø 500 and 650 mm.

Flatwork ironers | Ø 200

ROLLER DIAMETER	HEATING	ROLLER LENGTH		
		1400 mm	1600 mm	2000 mm
Ø 200 mm	Electric	PS-20/140 M	PS-20/160 M	PS-20/200 M

Flatwork ironers | Ø 325

ROLLER DIAMETER	HEATING	ROLLER LENGTH		
		1400 mm	1600 mm	2000 mm
Ø 325 mm	Electric and gas	PS-35/140 M	PS-35/160 M	PS-35/200 M

Flatwork ironers | Ø 325 - PLUS

ROLLER DIAMETER	HEATING	ROLLER LENGTH		
		2000 mm	2600 mm	3300 mm
Ø 325 mm	Electric and gas	PS-35/200 M PLUS	PS-35/260 M PLUS	PS-35/330 M PLUS

Flatwork ironers | Ø 500

ROLLER DIAMETER	HEATING	ROLLER LENGTH		
		2000 mm	2600 mm	3300 mm
Ø 500 mm	Electric, gas and steam	PSP-50/200 TP2	PSP-50/260 TP2	PSP-50/330 TP2
Ø 500 mm	With rear delivery With length folder	PSP-50/200 TP2	PSP-50/260 TP2	PSP-50/330 TP2

Flatwork ironers | Ø 650

ROLLER DIAMETER	HEATING	ROLLER LENGTH		
		2000 mm	2600 mm	3300 mm
Ø 650 mm	Electric, gas and steam	PSP-65/200 TP2	PSP-65/260 TP2	PSP-65/330 TP2
Ø 650 mm	With rear delivery With length folder	PSP-65/200 TP2	PSP-65/260 TP2	PSP-65/330 TP2

Designed to meet the needs of hotels, healthcare institutions, residential care homes and laundries.

Drying / Ironing Ø 200



Roller diameter

200 mm



Flatwork ironer

Ø 200 mm

Characteristics

- Drying and ironing in one single operation.
- Front feed and delivery of linen.
- Stainless steel and grey skin plate panels.
- Working width 1,40 m / 1,60 m / 2 m.
- M control easy-to-use.
- Nomex belts as standard.
- Ironing speed: 1,5-6 mts/min.
- Better collection of the linen.
- Easy installation.

Drying / Ironing Ø 325



Roller diameter

325 mm



Flatwork ironer Ø 350 mm

Characteristics

- Drying and ironing in one single operation.
- Front feed and delivery of linen.
- Stainless steel and skin plate panels.
- Ø 325 mm models with electric and gas heating.
- Working width 1,40 m / 1,60 m / 2 m.
- M control easy-to-use.
- Ironing speed: 1,5-10 mts/min.

Options

- Smart system: moisture control.
- Nickel-plated cylinder.

Flatwork ironer PLUS Ø 350 mm

Characteristics

- Drying and ironing in one single operation.
- Front feed and delivery of linen.
- Stainless steel and skin plate panels.
- Ø 325 mm models with electric and gas heating.
- Working width 2 m / 2,60 m / 3 m.
- Control: microprocesador M de fácil uso.
- Ironing speed: 1,5-12 mts/min.

Options

- Smart system: moisture control.
- Nickel-plated cylinder.



M Control

3 selectable operating modes:

- **Manual Mode:** selection of speed and temperature.
- **Auto Mode:** automatic adjustment of the ironing speed according to the temperature.
- **Smart-System (option in Ø 325):** automatic adjustment of ironing speed according to residual moisture, energy saver.



Robust

- **Roller with inverter:** delicate operation to prevent wear of belts and mechanical elements.
- **Panels in skin plate and stainless steel:** long-lasting.
- **Nomex feed and ironing belts: resistant to high temperatures.**
- **Option:** chrome-plated cylinder, anti-corrosion and longer-lasting (not available in 200 mm model).



Versatility

Radiant gas model: flexibility for increased production and better adaptation to high altitudes.



Ergonomics

- **Acoustic comfort:** max 65 dB.
- Skin plate and stainless steel panels: easy to clean, more hygienic.
- Stainless steel trays.
- **Height adjusted for feeding:** 990 mm.
- **Small size:** compact design to save space.



Efficiency

- **Smart-System:** automatic adjustment of ironing speed according to residual moisture, energy saver (option in Ø 350 mm).
- **Excellent heat conduction** thanks to roller fabric and thickness: increased control of energy dissipation.
- **Automatic stop at 80 °C:** extends lifetime of ironing belts.
- Gas circuit in lower section, reducing energy consumption.
- Precise temperature control thanks to the microprocessor: low energy consumption.
- Models with **radiant gas burner:** production increased by 25%, savings in time and energy.



Maintenance

- **Easy access to all the components** on both sides of the machine.
- **Compact design:** fits in many different spaces, the optional ironer is also included in the unit.





M Control

A simple, precise and intuitive microprocessor.

3 selectable operating modes

- **Auto Mode:** selection of speed and temperature.
- **Manual Mode:** automatic adjustment of the ironing speed according to the temperature selected.
- **Smart-System** (option in Ø 325).



Adjustable ironing speed

Adjustable ironing speed from 1 to 12 m/min.
(*check technical data chart).

Precise working temperature

Adjustable temperature from 1 to 180°C (Max).
Recommended working temperature is 160°C.



Robust

Designed to be long-lasting.

Roller with frequency variator

Gentle operation to prevent the wear of the belts and other mechanical elements.

Feeding and ironing belts in NOMEX

Resistant to high temperatures.

Stainless steel and skin plate panels

Long-lasting.

Nickel-plated cylinder optional

Anti-corrosion and long-lasting.



Efficiency

The flatwork ironers are equipped with features to save energy and time.



Smart System

Automatic adjustment of ironing speed according to residual moisture, energy saver (optional in Ø 325 mm).



Good heat conduction

Thanks to the roller fabric and thickness: greater control of energy dissipation.



Automatic shutdown at 80 °C

Extends the belt lifetime.



Reduction of energy consumption

Via the smoke circuit through the lower section.



Gas model with radiant burner

Increases production by 25%, offering savings in time and energy.

Washing

Investment
8%

Drying

Investment
7%

Ironing

Investment
19%

100%

Energy
32%

Water
13%

Detergent
47%

Energy
93%

Energy
81%

*Example of a standard laundry with 50% flat linen and 50% towelling, during the first 10 years of life.




Ergonomics

Fagor Professional seeks user comfort the operator.

Appropriate height for the introduction of clothing

990 mm.



Easy-to-use microprocessors

M Control with speed and temperature selection.

Acoustic comfort

65 dba max.

Compact design

Saves space, fits in many premises.

Panels in skin plate and stainless steel

Easy to clean, more hygienic
(complies with RABC standard).

Motor with variator

Provides gentle and gradual acceleration.





Maintenance

Fagor Professional's flatwork ironers are designed to offer the customer easy maintenance and repairs.

Single electric connection

Compact dimensions

Fits in any space.

Easy access to all the components

On both sides of the machine.




Drying / Ironing / Folded



Roller diameter

500 mm



Flatwork ironer

Ø 500 mm

Characteristics

- Drying and ironing in one single operation.
- Front feed and delivery of linen.
- Heating: electric, gas (radiant or atmospheric burner) and steam.
- Roller width: 2 m / 2.60 m / 3.30 m.
- Control: Touch Plus Control (TP2) microprocessor with 7" touch screen (5 predefined programmes).

Options

- Smart system.
- HPS system: high production system (includes Smart System).
- Length folder incorporated.
- Rear delivery.
- Nickel-plated cylinder.

Drying / Ironing / Folded



Roller diameter

650 mm



Flatwork ironer Ø 650 mm

Characteristics

- Drying and ironing in one single operation.
- Front feed and delivery of linen.
- Heating: electric, gas (radiant or atmospheric burner) and steam.
- Roller width: 2 m / 2.60 m / 3.30 m.
- Control: Touch Plus Control (TP2) microprocessor with 7" touch screen (5 predefined programmes).
- HPS system: high production system (includes Smart System).

Options

- Length folder incorporated.
- Rear delivery.
- Nickel-plated cylinder.



Touch Plus TP2 control

- **Easy-to-use and totally programmable 7" touch screen.**
- **38 languages available.**
- **5 predefined programmes**, option to create infinite number.
- **USB connection.** Free PC software for programming, traceability, data analysis...



Robust

- **Roller with inverter:** delicate operation to prevent wear of belts and mechanical elements.
- **Panels in skin plate and stainless steel:** long-lasting.
- **Nomex feed and ironing belts: resistant to high temperatures.**
- **Option:** nickel-plated cylinder, anti-corrosion and longer-lasting.



Versatility

- **Rear delivery.**
- **Length folder incorporated** (optional).
- Option to add a cross folder and stacker.
- Radiant gas model: flexibility for increased production and better adaptation to high altitudes.



Ergonomics

- **Acoustic comfort:** max 65 dB.
- Skin plate and stainless steel panels: easy to clean, more hygienic.
- Stainless steel trays.
- **Height adjusted for feeding:** 1.120 mm.
- **Small size:** compact design to save space.



Efficiency

- **Smart-System:** automatic adjustment of ironing speed according to residual moisture, energy saver (option in Ø 500 mm).
- **HPS system:** automatic adjustment of ironing speed, reduced while feeding linen and increased for more production, up to 15 m/min (option in Ø 500 mm). Includes Smart System.
- **Excellent heat conduction** thanks to roller fabric and thickness: increased control of energy dissipation.
- **Automatic stop at 80 °C:** extends lifetime of ironing belts.
- Gas circuit in lower section, reducing energy consumption.
- Precise temperature control thanks to the microprocessor: low energy consumption.
- Models with **radiant gas burner:** production increased by 25%, savings in time and energy.



Maintenance

- **Easy access to all the components** on both sides of the machine.
- **Compact design:** fits in many different spaces, the optional ironer is also included in the unit.
- Ironing trays for easy maintenance.
- **A single electric connection and smoke output.**
- **Remote communication:** better and faster technical service.





Touch Plus Control

A microprocessor designed to offer efficiency, versatility and connectivity.

Programmer and easy-to-use and totally programmable 7" touch screen



38 languages

Easy to configure, thanks to the Fagor Professional goal to be accessible to everyone.

USB connection

Free PC software for programming, traceability, data analysis...





Robust

Designed to be long-lasting.

Roller with frequency variator

Gentle operation to prevent the wear of the belts and other mechanical elements.

Stainless steel and skin plate panels


Long-lasting.

Feeding and ironing belts in Nomex

Resistant to high temperatures.

Nickel-plated cylinder optional

Anti-corrosion and long-lasting.





Efficiency

The flatwork ironers are equipped with features to save energy and time.



Smart System

Automatic adjustment of ironing speed according to residual moisture, energy saver (optional in Ø 500 mm, standard in Ø 650 mm).



HPS system

Option to configure 3 levels of saving, standard.



Good heat conduction

Thanks to the roller fabric and thickness: greater control of energy dissipation.



Automatic shutdown at 80°C

Extends the belt lifetime.



Reduction of energy consumption

Via the smoke circuit through the lower section.



Gas model with radiant burner

Increases production by 25%, offering savings in time and energy.



Precise control of temperature

Thanks to the microprocessor (except in steam mod.): low energy consumption.



**GREEN
EVOLUTION**
FOR A
SUSTAINABLE
FUTURE.



Versatility

Models with rear delivery and length folder to meet every need.

Rear delivery


Optionally with the length folder incorporated into the unit.

Length folder incorporated

Same dimensions for Ø 500 and 650 mm models, as option.


Cross folder

Possibility to add independent cross folder and stacker to increase productivity (only models with rear delivery and folder).



Radiant gas burner

Flexibility for improved production and adaptation to high altitudes, with less oxygen.






Ergonomics

Fagor Professional seeks user comfort the operator.

Appropriate height for the introduction of clothing

1120 mm.



Easy-to-use microprocessors

Touch Plus Control, fully programmable.

Acoustic comfort

65 dba max.

Compact design

Saves space, fits in many premises.

Panels in skin plate and stainless steel

Easy to clean, more hygienic (complies with RABC standard).

Motor with variator

Provides gentle and gradual acceleration.





Maintenance

Fagor Professional's flatwork ironers are designed to offer the customer easy maintenance and repairs.

Single electric connection

Compact dimensions

Fits in any space.

Easy access to all the components

On both sides of the machine.

Technical service menu with Touch Plus Control TP2

Remote Communication

Option only with Touch Plus Control, perfect for quick response.



Technical data

		Ø 200				Ø 325					
		UNIT.	PS-20/140	PS-20/160	PS-20/200	PS-35/140	PS-35/160	PS-35/200	PS-35/20 PLUS	PS-35/260 PLUS	PS-35/330 PLUS
GENERAL DATA											
Theoretical production 45% humidity	Heating Elec. power	Kg/h	12	16	22	18	30	40	50	60	85
	Heating atmospheric gas	Kg/h	----	----	----	22	32	42	----	----	----
	Heating radiant gas	Kg/h	----	----	----	----	----	----	65	75	100
Evaporation power		l/h	5,4	7,2	9,9	8,1	13,5	18	29	34	45
Ø Roller		mm	200	200	200	325	325	325	325	325	325
Service width		mm	1400	1600	2000	1400	1600	2000	2000	2600	3300
Feeder belts-floor height		mm	990	990	990	990	990	990	990	990	990
Operating speed		mt/min	1.5-6	1.5-6	1.5-6	1.5-10	1.5-10	1.5-10	1,5-12	1,5-12	1,5-12
Electric control			M			M			M		
No of Programmes		Nº	2 standard modes			2 standard modes			2 standard modes		
Folder + rear delivery		Nº	No	No	No	No	No	No	No	No	No
Increased surface in contact with linen		º	270	270	270	270	270	270	270	270	270
POWERS											
Electric	Heating Power	kW	10,5	12	18	12	16,2	21	31,5	40,5	54
	Total electrical power	kW	10,84	12,34	18,37	12,37	16,57	21,49	32,27	42,27	54,77
Gas	Heating Power	kW	----	----	----	14	22,5	30	40	55	69
	Total electrical power	kW	----	----	----	0,37	0,37	0,49	0,77	0,77	0,77
Roller motor power		kW	0,28	0,28	0,28	0,28	0,28	0,28	0,41	0,41	0,41
Fan motor power		kW	0,09	0,09	0,09	0,12	0,12	0,12 x2	0,18 x 2	0,18 x 2	0,18 x 2
CONNECTIONS											
Ø gas inlet		BSP	----	----	----	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
NET DIMENSIONS											
Width		mm	1878	2128	2478	1952	2202	2552	2552	3202	3852
Depth (without trays)		mm	444* (666)	444* (666)	444* (666)	686	686	686	686	686	686
Height		mm	1110	1110	1110	1112	1112	1112	1112	1112	1112
Weight		Kg	180	203	237	330	385	435	445	545	655
DIMENSIONS WITH PACKAGING											
Width		mm	2130	2340	2780	2340	2340	2780	2780	3430	3980
Depth (without trays)		mm	770	770	770	770	770	770	770	770	770
Height		mm	1400	1400	1400	1400	1400	1400	1400	1400	1400
Weight		Kg	220	240	275	365	405	458	458	585	700
Volume		m³	2,30	2,52	3,00	2,52	2,52	3,00	3,00	3,70	4,29
OTHERS											
Steam outlet		Nº	1	1	1	1	1	2	2	2	2
Ø Steam outlet		mm	83	83	83	98	98	98	98	98	98
Intake air flow		m³/h	300	300	300	500	500	1000	1000	1000	1000
Sound level		dB	55	55	55	60	60	63	63	63	63

Technical data

			Ø 500			Ø 650		
UNIT.			PSP-50/200 TP2	PSP-50/260 TP2	PSP-50/300 TP2	PSP-65/200 TP2	PSP-65/260 TP2	PSP-65/330 TP2
GENERAL DATA								
Producción teórica 45% humedad	Heating Elec. power	Kg/h	68	84	115	90	115	160
	Heating atmospheric gas	Kg/h	68	84	115	-----	-----	-----
	Heating radiant gas	Kg/h	82	100	138	104	132	184
	Heating Steam power	Kg/h	37	45	62	78	115	132
Evaporation power		l/h	35 - 49	42 - 56	56 - 84	45-63	55 - 73	73 - 110
Ø Roller		mm	500	500	500	650	650	650
Service width		mm	2000	2600	3300	2000	2600	3300
Feeder belts-floor height		mm	1170	1170	1170	1170	1170	1170
Operating speed		mt/min	0,5-8	0,5-8	0,5-8	0,5-15	0,5-15	0,5-15
Electric control			TP2			TP2		
No of Programmes		Nº	5 standard modes			5 standard modes		
Folder + rear delivery		Nº	Opc	Opc	Opc	Opc	Opc	Opc
Increased surface in contact with linen		°	310	310	310	310	310	310
POWERS								
Electric	Heating Power	kW	31,5	40,5	54	42	54	72
	Total electrical power	kW	32,16	41,41	54,91	43,05	55,05	73,05
Gas	Heating Power	kW	40	55	69	52	69	78
	Total electrical power	kW	0,62	0,87	0,87	1,05	1,05	1,05
Steam	Heating Power	kW	50	64	81	60	76	97
	Total electrical power	kW	0,62	0,87	0,87	1,05	1,05	1,05
Roller motor power		kW	0,37	0,37	0,37	0,55	0,55	0,55
Fan motor power		kW	0,25	0,25 x2	0,25 x 2	0,25 x 2	0,25 x2	0,25 x 2
Additional elec. power mod. SPE			0,13	0,13	0,13	0,13	0,13	0,13
Additional elec. power mod. LF		kW	0,23	0,23	0,23	0,23	0,23	0,23
Additional elec. power mod. LFRE		kW	0,33	0,33	0,33	0,33	0,33	0,33
CONNECTIONS								
Ø gas inlet		BSP	1"	1"	1"	1/2"	1/2"	1/2"
Ø steam inlet		BSP	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Ø Condensation (steam models)		BSP	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
NET DIMENSIONS								
Width		mm	2845	3445	4145	2845	3445	4145
Depth (without trays)		mm	1070	1070	1070	1070	1070	1070
Height		mm	1420	1420	1420	1420	1420	1420
Weight		Kg	930	1180	1430	1189	1517	1765
DIMENSIONS WITH PACKAGING								
Width		mm	3145	3745	4445	3145	3745	4445
Depth (without trays)		mm	1153	1153	1153	1153	1153	1153
Height		mm	1672	1672	1672	1672	1672	1672
Weight		Kg	972	1470	1480	1231	1567	1815
OTHERS								
Steam outlet		Nº	1	2	2	2	2	2
Ø Steam outlet		mm	153	153	153	153	153	153
Intake air flow		m³/h	600	1200	1200	1200	1200	1200
Sound level		dB	65	65	65	65	65	65

STD Mod. standard.

SRE Mod. with rear exit without folder.

LF Mod. with built-in lengthfolder + front exit.

LFR Mod. with Built-in lengthfolder + rear and front exit.



ONNERA GROUP



ACTIVELY SUPPORTING

