# FINISHING

—

# FINISHING TABLES WITHOUT BOILER MP - A/AS/ASV

## CHARACTERISTICS

- 3 variants
  - A: vacuum
  - S: blowing
  - V: up steaming
- Vacuum ironing table + iron, with electrically heated board and suction.
- Adjustable temperature of the board by means of a thermostat.
- Built-in single phase suction unit.
- Working table dimensions (1.200 x 400 x 250 mm).
- Works by means of a pedal.
- Electrical heating.

## OPTIONS

- Sleeve arm.
- Steam gun.
- Sliding trolley with light.

# TECHNICAL DATA
# FINISHING TABLES WITHOUT BOILER | MP-A/AS/ASV

| | U. | MP-A | MP-AS | MP-ASV |
|---|---|---|---|---|
| CAPACITY | | | | |
| Boiler | - | No | No | No |
| Boiler capacity | l | - | - | - |
| Board dimensions | mm | 1.200 x 400 x 250 | 1.200 x 400 x 270 | 1.200 x 400 x 250 |
| OPTIONS | | | | |
| Swinging arm with suction and heated sleeve shape | - | Opc | Opc | Opc |
| Steam gun | - | Opc | Opc | Opc |
| Sliding trolley with balancer and lighting | - | Opc | Opc | Opc |
| Second steam iron assembly | - | Opc | Opc | Opc |
| POWER | | | | |
| Vacuum Motor | kW | 0,45 | 0,45 | 0,45 |
| Pump Motor | kW | - | - | - |
| Iron Heater | kW | 0,83 | 0,83 | 0,83 |
| Board heater | kW | 1 | 1 | - |
| Sleeve-arm heater (option) | kW | 0,09 | 0,09 | 0,09 |
| CONNECTIONS | | | | |
| Ø Water inlet | BSP | - | - | - |
| Ø Steam inlet | BSP | 1/4” | 1/4” | 3/8” |
| Steam pressure | BAR | - | - | - |
| Steam Consumption | Kg/h | 5 | 5 | 10-15 |
| Ø Air inlet | BSP | - | - | - |
| Air pressure | BAR | - | - | - |
| Air Consumption | Nl/m | - | - | 5 |
| DIMENSIONES / DIMENSIONES CON EMBALAJE | | | | |
| Width / Width | mm | 1.480/1.520 | 1.500/1.520 | 1.680/1.880 |
| Depth / Depth | mm | 480/580 | 600/580 | 580/680 |
| Height / Height | mm | 930/1.120 | 1.800/1.120 | 920/1.270 |
| Net weight / Gross weight | kg | 66/82 | 78/94 | 110/134 |
| Volume | $m^3$ | 3,20/5,19 | 3,88/6,23 | 4,68/7,43 |
| OTHERS | | | | |
| Voltage | Hz | 230V I 50 | 230V I 50 | 230V I 50 |
| Sound level | dB | 68 | 70 | 75 |

# FINISHING

—

# FINISHING TABLES WITH BOILER
# MP-4 A-C / MP-A/AS/ASV - C

## CHARACTERISTICS

### 3 VARIANTS:
- A: vacuum
- S: blowing
- V: up steaming

### MP-4 A-C
- Utility ironing table with electrically heated board and suction unit.
- Version with built-in electric steam boiler, water pump, water feeding tank and electric steam iron.
- Built-in suction unit controlled by foot pedal.
- Adjustable board temperature by thermostat.
- Pedals on both sides of the table.
- Electric boiler with water feeding and automatic steam production.Working pressure: 2,6 bar.
- Manual feeding of water tank.
- Voltage: 230V I 50Hz

### MP-A/AS/ASV - C
- Utility ironing table with suction and electrically heated board, controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1200x400x250).
- Automatic water feeding.

## OPTIONS

- Sleeve arm.
- Steam gun.
- Sliding trolley with light.
- Second iron.

# TECHNICAL DATA
# FINISHING TABLES WITH BOILER | MP-4 A-C / MP-A/AS/ASV - C

| | UNIT. | MP-4 A-C | MP-A-C | MP-AS-C | MP-ASV-C |
|---|---|---|---|---|---|
| CAPACITY | | | | | |
| Boiler | - | Yes | Yes | Yes | Yes |
| Boiler capacity | l | 4 | 5 | 5 | 7 |
| Board dimensions | mm | 1.100 x 380 x 270 | 1.200 x 400 x 250 | 1.200 x 400 x 270 | 1.200 x 400 x 250 |
| OPTIONS | | | | | |
| Swinging arm with suction and heated sleeve shape | - | Opc | Opc | Opc | Opc |
| Steam gun | - | - | Opc | Opc | Opc |
| Sliding trolley with balancer and lighting | - | - | Opc | Opc | Opc |
| Second steam iron assembly | - | - | Opc | Opc | Opc |
| POWER | | | | | |
| Vacuum Motor | kW | 0,13 | 0,45 | 0,45 | 0,45 |
| Pump Motor | kW | - | - | - | 0,75 |
| Iron Heater | kW | 0,8 | 0,83 | 0,83 | 0,83 |
| Board heater | kW | 0,7 | 1 | 1 | - |
| Boiler Heater | kW | 1,45 | 3,9 | 3,9 | 6-7,5 |
| Sleeve-arm heater (option) | kW | 0,09 | 0,09 | 0,09 | 0,09 |
| CONNECTIONS | | | | | |
| Ø Water inlet | BSP | - | 3/8” | 3/8” | 3/8” |
| Ø Boiler exhaust (with boiler) | BSP | - | 3/8” | 3/8” | 3/8” |
| Ø Steam inlet | BSP | - | - | - | - |
| Steam pressure | BAR | 2,8 | 2,8 | 2,6 | 4,5 |
| Steam Consumption | Kg/h | - | - | - | - |
| Ø Air inlet | BSP | - | - | - | 1,4” |
| Air pressure | BAR | - | - | - | 4-8 |
| Air Consumption | Nl/m | - | - | - | 5 |
| DIMENSIONES / DIMENSIONES CON EMBALAJE | | | | | |
| Width / Width | mm | 1.380/1.300 | 1.550/1.520 | 1.500/1.520 | 1.680/1.880 |
| Depth / Depth | mm | 380/540 | 580/580 | 600/580 | 580/680 |
| Height / Height | mm | 930/1.160 | 950/1.140 | 1.800/1.120 | 920/1.270 |
| Net weight / Gross weight | kg | 43/57 | 87/103 | 100/116 | 141/165 |
| Volume | $m^3$ | 0,49/0,81 | 0,85/1,01 | 1,62/0,99 | 0,90/1,62 |
| OTHERS | | | | | |
| Voltage | Hz | 230V I 50 | 230/400V III 50 | 230V I 230/400V III 50 | 230/400V III 50 |
| Sound level | dB | 70 | 68 | 70 | 75 |