



FINISHING

SPOTTING TABLES DES-F / MINI-DES



DES-F



MINI-DES

CHARACTERISTICS

DES-F

- Cold spotting table with built-in suction unit.
- Cold spotting table.
- Featuring two cold spotting spray guns with independent circuits, two receptacles for liquids, hose support and swinging arm with suction and spotting shape out of stainless steel AISI 304.
- Board out of stainless steel AISI 304.
- Board dimensions: de 800 x 260 x 175 mm.
- Electric connection: 230V I+N / 50-60 Hz.
- With compressor: 230/400V III 50Hz.
- It needs compressed air (200 NI/min).

MINI-DES

- Cold spotting table with built-in suction unit.
- Equipped with two receptacles for liquids and one spotting spray gun.
- One working pedal.
- Electric connection: 230V I+N / 50-60 Hz.
- It needs compressed air.

OPTIONS

- Compressor for DES-F
- Air-steam gun for DES-F
- Trolley for MINI-DES.

TECHNICAL DATA

SPOTTING TABLES | DES-F / MINI-DES

	UNIT.	DES-F	DES-F GC	MINI-DES
GENERAL DETAILS				
Board dimensions	mm	800 x 260 x 175	800 x 260 x 175	400 x 200 x 35
Boiler	-	NO	NO	NO
Compressor	-	OPT	YES	-
Steam gun	-	OPT	OPT	-
POWER				
Vacuum motor	HP	0,6	0,6	0,13
Compressor motor	kW	2	2	-
CONEXIONES				
Ø Steam inlet	BSP	3/8"	3/8"	-
Ø Condensate outlet	BSP	3/8"	3/8"	-
Steam supply pressure	BAR	4-6	4-6	-
Steam working pressure	BAR	5	5	-
Steam consumption	Kg/h	3-5	3-5	-
Ø Air inlet	BSP	1/4"	1/4"	1/4"
Ø Air outlet	mm	90	90	-
Steam pressure	BAR	5-8	5-8	-
Steam Consumption	Kg/h	6	6	6-8
Air Consumption	NI/m	150	150	30
DIMENSIONES / DIMENSIONES CON EMBALAJE				
Net width / Gross width	mm	1.270 / 1.300	1.270 / 1.300	670 / 650
Net depth / Gross depth	mm	600 / 650	600 / 650	320 / 330
Net height / Gross height (antenna folded)	mm	1.900 / 1.160	1.900 / 1.160	680-1.500 / 335
Net weight / Gross weight	Kg	44 / 53	78 / 118	13 / 16
Volume	m ³	1,45 / 0,98	1,45 / 0,98	0,14 / 0,15
OTROS				
Voltage	V	230V 1~ 50-60	230/400 V 3~ 50-60 Hz	230V 1~ 50-60
Sound level	dB	<70	<70	65

